



Visit product page



FOS PAR 18X10WPRO IP65

L004961

Weatherproof aluminium led par with IP connectors , Beam aperture: 30°, 18 RGBW 10w LEDs (4in1) Dimmer: 0-100% stop/strobe effect, aluminium 4kg, noiseless cooling system.

TECHNICAL DETAILS

Light Source/Optics

18 RGBW 10w LEDs (4in1)
Average lifespan: 50000 Hours
Beam aperture: 30°
Noiseless cooling system

Effects

RGBW dimming/fade.
RGBW color mixing
Auto programs with speed adjustment
Preset colors
Dimmer: 0-100% linear dimming
Adjustable speed stop/strobe effect (1-10 flash/sec)

Control

Control modes: DMX 512 (4 / 8 DMX channels), sound activated, auto mode
Stand-alone mode and Master/Slave modes
Data in/out: 3 pin XLR IP65

Installation/Dimension Details

Voltage: 90 to 240 Volts – 50/60Hz

Power consumption: 200 Watt

IP65 cables input and output

Double yoke system, which act as a floor stand

Operating positions: all (device on floor or fixed to a support). IP65 protection from dust and water, suitable for outdoor applications.

Maximum permitted ambient temperature (Ta max): 45°C (113°F). Minimum permitted ambient temperature authorized (Ta min): -10°C (14°F).

Dimensions: Par diameter 22 cm, depth 12 cm, height (with yoke in vertical position 26 cm).

Weight: 4,6 Kg.

PHOTOS



PRODUCT VIDEO



ACCESSORIES



FOS Case 8in1 PAR PRO

Flight case with wheels for
8pcs Pro series and T



www.fos-lighting.eu

