



Visit product page



## FOS TOURING PAR 7X15 IP HEX

L005528

Weatherproof aluminium led par with IP True powercon connectors , Beam aperture: 25°, 7 RGBW+Amber+UV 15w LEDs (6 in1)Dimmer: 0-100% stop/strobe effect, aluminium 3kg, noiseless cooling system.

### TECHNICAL DETAILS

#### Light Source / Optics

Light source: 7x 15 Watt RGBWAUV 6 in 1 LEDs.  
Beam angle: 25°.

#### Effects

RGBWAUV color mixing.  
Dimmer from 0 to 100%.  
Strobe effect with variable speed.  
Color macros and effects.

#### Control

Manual (on-board control), sound mode, auto, sound and DMX.  
DMX control with 6 or 10 channels.

#### Installation / Dimension details


Power supply: 100/240 Volt AC, 50/60 Hz.  
Power consumption: 105 Watt.  
Protection rate against dust and water: IP65  
Net weight: 3,1 Kg.  
Dimensions (projector only): 165 mm length x 173 mm width x 150 mm height.

Dimensions (with the yoke and projector in vertical position): 215 mm lenght x 150 mm width x 240 mm height.

PHOTOS



PRODUCT VIDEO



[www.fos-lighting.eu](http://www.fos-lighting.eu)

