



[Visit product page](#)



## FOS TV BICOLOR PANEL

L005613

Studio Bicolor Soft panel, 1200 SMD leds 0.2 Watts, Color temperature: 3200K-5600K adjustable (warm white to cold white), high CRI (Ra?95) and high brightness LED, Beam angle: 120degree, DMX channel: 4CH/5CH , Low Noise Operation, 9kg.

### TECHNICAL DETAILS

#### Light source / Optics

LED panel with adjustable colour temperature from 3200 to 5600 Kelvin.

Color: Warm to Cold white.

1200 pieces of 0,2 Watt each, SMD LEDs.

Lifespan: 50.000 hours

High colour rendering index:  $\geq 92$  Ra CRI

Beam angle: 120 degrees.

Barndoors included.

#### Control

DMX channel: 4CH/5CH

Control mode: DMX-512, Demo mode, Manual

Control panel: LCD display + 4 buttons

0-100% accurate linear dimmer

Strobe Function

#### Dimensions / Installation details

Power supply: AC100/240 Volt AC, 50/60 Hz.

Powercon in/out

Power Consumption: 200 W  
IP Rating: IP20  
Noice Level (dB): 0  
Aluminum alloy housing construction.  
Operating temperatures: -25 to +45 degrees.  
Dimensions: 480 mm x 270 mm x 280 mm with the yoke vertical, 130 mm -fixtures only- height  
Weight: 9 Kg.

**Photometric Data**

**Measuring Distance : 1 meter**

Warm white WW

Color Temperature (K): 2968  
Illuminance (lx): 4081  
CRI (Ra): 91.1  
TLCI (Qa): 94  
Flicker Frequency (Hz): 142  
Flicker(%): 0

Cool White CW

Color Temperature (K): 5393  
Illuminance (lx): 3884  
CRI (Ra): 98.7  
TLCI (Qa): 97  
Flicker Frequency (Hz): 50  
Flicker(%): 0


WW + CW

Color Temperature (K) : 3890  
Illuminance (lx): 5554  
CRI (Ra): 96.3  
TLCI (Qa): 96  
Flicker Frequency (Hz): 75  
Flicker (%): 2

## PHOTOS



## PRODUCT VIDEO



[www.fos-lighting.eu](http://www.fos-lighting.eu)

