



[Visit product page](#)



FOS 3000RGB DIODE

L004791

Professional Full Diode RGB Animation Laser, R:400mW + G:500mW + B:1600mW Analog Modulation (total 2.5W), R: 635nm+G: 520nm+B:450nm, scanner 25KPPS, $\pm 20^\circ$

TECHNICAL DETAILS

Light Source/Optics

400 mW RED (635 nm), 500 mW GREEN (520 nm), 1600 mW BLUE (450 nm)

Beam angle: 20°

25K high speed optical scanner

Effects

Beam show & animated graphics show patterns

Control

Control modes: DMX 512 (17 DMX channels), sound activated, auto mode

Stand-alone mode and Master/Slave modes

Program mode (load from SD card)

Data in/out: 3 pin XLR

ILDA for PC control

Installation/Dimension Details

Operating positions: all (device on floor or fixed to a support)

Maximum permitted ambient temperature (T_a max): 50°C (113°F). Minimum permitted ambient temperature authorized (T_a min): -10°C (14°F).

Voltage: 110 to 250 Volts – 50/60Hz

Power consumption: 150 Watt


Dimension: 22 x 28 x 16 cm

Weight: 6,5 kg

PHOTOS



PRODUCT VIDEO



www.fos-lighting.eu

