



[Visit product page](#)



FOS SPARK JET PRO

L005544

The best sparkle machine with RDM function and density channel, Adjustable Height 1.5-5M , Lineary Adjustable Density 30-100%, Maximum Single Continuous Duration 30s, Heat Up Time 5 Minutes , 5 Minutes , seetronic connectors, consumption 20-25g/Minute

TECHNICAL DETAILS

Technical Specifications

Power supply: 200/240V, 50/60 Hz.

Nominal power consumption: 600 W.

Heat up time: 5 minutes.

Powder tank capacity: 150g.

Linear density adjustment from 30 to 100 %.

Adjustable height from 1,5 to 5 meters.

Powder consumption: 20/25g per minute (maximum).

Maximum single continuous duration: 30s.

Controlled via DMX512.

Remote Control included

RDM support.

1,6 meter power cord (Seetronic).

Net weight: 8Kg.

Gross weight: 10Kg.

Dimensions: 215 x 213 x 262 mm.

Package dimensions: 270 x 250 x 330 mm.

Granule: Spark Fabrica Granule

PHOTOS



PRODUCT VIDEO



ACCESSORIES



FC-TP-PDC-5

Professional

TruePowercon/ DMX cable 5 meter.



FC-TP-PDC-3

Professional

3 meter.



FC-TP-PDC-1.5

Professional

1.5 meter.



FOS Case Spark Jet PRO

Flight case with wheels for
4 pcs Spark Jet PRO wi



FOS Spark Jet Smart Console

RDM Touch Screen DMX
controller, Monitor
temperatu



FOS Spark Powder

Titanium Powder 150 gr
and RFID card for Spark Jet



www.fos-lighting.eu

