



[Visit product page](#)



TILOS L SUB

L005682

Professional plywood active vented subwoofer 2 X10 inch for the Tilos Column system, 500w Rms, 121 dB Spl, German Engineering D class amplifier, multiple DSP ,XLR input, sat mode select, Frequency response 50-200 Hz.

TECHNICAL DETAILS

Technical Specifications

Active vented subwoofer.
Inputs: XLR/TRS combo jack.
Output: XLR balanced line, XLR LINK, SAT Out.
250 Watt RMS (subwoofer) & 250 Watt RMS (satelite).
Subwoofer volume control, +4 / -10 dB sensitivity switch.
Power Input: 115 / 230 Volt AC, 50 / 60 Hz switchable.
German Engineering Class D amplifier + switching power supply.
Sat Mode selection.
Power / clip indicator.
DSP effect processor.
Excellent compressor.
Frequency response: 50 - 200 Hz.
Max. output SPL: 118 dB.
Driver: 10" subwoofer, 2,5" VC 45 oZ.
PLY cabinet with black painted finish.
1,2 mm steel mesh.
Packing Dimensions: 61,5 x 45,5 x 76 cm.
Gross Weight: 27,5 Kg.

Packing Details

51 x 40.5 x 51 cm - 13kg

PHOTOS



PRODUCT VIDEO




ACCESSORIES



iCover Tilos L

Cover for Tilos L



www.fos-lighting.eu

