Visit product page



TINOS SYSTEM

L005918

Column PA system, lightweight portable and feature packed. speaker 1x8 sub, 6x2.75 hf, 120 dB SPL , 125W (sub)+125w (sat), Frequency response 50-20KHZ, German Engineering Class D amplifier, internal mixer with reverb and bluetooth,

TECHNICAL DETAILS

Technical Specifications

Inputs: XLR/TRS combo jack, stereo RCA & 1/8" AUX input / Bluetooth.
Line out: XLR balanced 3 channel mixer.
RMS 125 Watt (sub) 7 125 Watt (sat).
Volume control for each channel.
Power input: 100 /240 Volt, 50/60 Hz.
German Engineering Class D amplifier + switching power supply.
2 band EQ.
Excellent compressor.
Power / clip indicator.
Frequency response: 55 / 200 Hz.
Max output SPL: 114 dB (at max. amp output).

Subwoofer

Active vented subwoofer.
Driver: 8" subwoofer, 1,5" vc 33oZ (T1SW8).
PP plastic cabinet.
1 mm steel mesh.

Satellite

Passive full-range speaker
Frequency response: 180 - 20 kHz.
Directivity: 90° H x 10° V
Max. output SPL: 114 dB.
Impedance: 4 Ohms.
Driver: 6x 2.75" full range line array.
PP plastic cabinet.
1 mm steel mesh.

Satellite dimensions: 11 x 20 x 85 cm, 5 Kg.
Subwoofer dimensions: 51 x 40,5 x 51 cm, 13 Kg.

Packing Details

Tinos S: 20 x 11 x 86 cm, 4,5 Kgs.
Tinos L: 51 x 41 x 51 cm, 13 Kgs.

PHOTOS











PRODUCT VIDEO

ACCESSORIES



iCover Tinos

Cover For Tinos System

IHOS INTELLIGENT AUDIO

www.fos-lighting.eu