



Visit product page



FOS 5000RGB DIODE

L004793

Professional Full Diode RGB Animation Laser, R:1000mW + G:1000mW + B:3000mW Analog Modulation (total 5W), R: 635nm+G: 520nm+B:450nm, scanner 40KPPS, $\pm 30^\circ$

TECHNICAL DETAILS

Light Source/Optics

1000 mW RED (635 nm), 1000 mW GREEN (520 nm), 3000 mW BLUE (450 nm)

Beam angle: 20°

40K high speed optical scanner

Effects

Beam show & animated graphics show patterns

Control

Control modes: DMX 512 (17 DMX channels), sound activated, auto mode

Stand-alone mode and Master/Slave modes

Program mode (load from SD card)

Data in/out: 3 pin XLR

ILDA for PC control

Installation/Dimension Details

Operating positions: all (device on floor or fixed to a support)

Maximum permitted ambient temperature (T_a max): 50°C (113°F). Minimum permitted ambient temperature authorized (T_a min): -10°C (14°F).


Voltage: 110 to 250 Volts – 50/60Hz

Power consumption: 150 Watt
Dimensions: 22 x 28 x 16 cm
Weight: 6,8 kg

PHOTOS



PRODUCT VIDEO



www.fos-lighting.eu

