



SPE-72/WS

Order No.: 0162310

PRODUCTINFOS

Weatherproof flush-mount full range speaker with dual cone, 20 W, 4 Ω

- Weatherproof speaker of compact size and a high power capability with a wide bandwidth and particularly brilliant reproduction due to a twin cone
- High-quality one-piece white plastic basket with magnetic sleeve
- Polypropylene cone and mica dual cone
- Rubber surround, supplied with matching plastic grille (to be glued in)
- Also suitable for PA applications in a damp environment and outdoors

TECHNICAL SPECIFICATIONS

SPE-72/WS

Impedance (Z) 4Ω

Frequency range 100-20,000 Hz

Resonant frequency (fs) 100 Hz
Power rating (RMS) 20 W
Peak music power output (MAX) 40 W



SPE-72/WS

SPL 86 dB/W/m
Mounting cutout Ø 73 mm
Mounting depth 37 mm

Dimensions Ø 90 mm x 50 mm

Outside diameter \emptyset 90 mm Width \emptyset 90 mm Depth 50 mm

Colour black/silver/white

Protective class IP65
Admiss. ambient temp. 0-40 °C
Weight 230 g
Packing unit 1
Type of speaker 75

Packing dimensions (W x H x L) 0.1 x 0.06 x 0.1 m

Gross weight 0.269 kg
Net weight 0.233 kg